

## SURFACE PROPERTIES

<b>Material</b>	Polyester Film
<b>Thickness (mm)</b>	0,050 ± 0,005
<b>Basic Weight (g/m<sup>2</sup>)</b>	70 ± 5
<b>Color</b>	White
<b>Smoothness</b>	Good
<b>Print Ability</b>	Good

## LINER PROPERTIES

<b>Material</b>	Polyester Release Film
<b>Thickness (mm)</b>	0,100 ± 0,007
<b>Basic Weight (g/m<sup>2</sup>)</b>	140 ± 7
<b>Color</b>	Transparent
<b>Smoothness</b>	Good
<b>Die Cuting</b>	Good

## PRESSURE SENSITIVE ADHESIVE PROPERTIES

<b>Adhesive</b>	Acrylic
<b>Thickness (mm)</b>	0,032 ± 0,002
<b>Dry Coating Weight (g/m<sup>2</sup>)</b>	32 ± 2
<b>Solvent Retention (wt%)</b>	2 ↓
<b>Initial Tack (no/ball)</b>	4 ↑
<b>180° Peel Adhesive (kgf/inch)</b>	1,2 ↑
<b>Release Force (gf/inch)</b>	20 ± 10
<b>Holding Power (hr/kg.inch)</b>	8 ↑
<b>Weather Resistance</b>	Good
<b>Temperature Range (°C)</b>	5~125
<b>Solvent Resistance</b>	Good

**Remark:** The technical data are based on reliable experiments carried out by the "company". Which however, are not to guarantee those properties and characteristics completely as specified therein, kindly study your purpose, condition and test this product properly before application